




Contact SignsSeen
 614-543-1397
 FAX: 614-543-9799
 TOLL FREE: 1-866-825-4735

SS16128 Tri-Color, Single or Double Line Message Sign



Cabinet Dimensions	Weight	LED Array	Max. Viewing	Height / Lines / Chars.* *Font and Character Dependant
39.3" x 6.5" x 3.25"	14 lbs.	16 x 128	200 ft.	4.75" /1 / 12 chars.
				2.0" /2/ 24 chars.
				1.4" /2/ 32 chars.

The **SS16128** is a ready-to-run indoor moving message sign board. Using 5mm Super bright tri-color LEDs, it can store up to 100 messages or a total length of characters not to exceed 7000. Ideal for retail outlets or POP locations. Pre-loaded graphics and special occasion messages included. Create your own animation and logos.

Multi-color message centers let you specify red, green and yellow characters or any combination of these to get you message across. Ideal to promote your business, safety messages, employee messages and more. Pre-programmed graphics are available to get the attention your business needs.

Features

- **16 Color Combinations:**
 - 3 basic colors
 - 5 rainbow colors
 - 8 mixture colors
 - Automatic color rotation (ACL)
- **9 Fonts Available Including WIDE and BOLD**
- **41 Display Modes**
 - 6 slide modes
 - 6 cover modes
 - 6 roll modes
 - 4 interlace-slide modes
 - 6 interlace-roll modes
 - 4 shutter modes
 - 9 special effect modes
 - AUTO display randomly selects one of the available display modes



Contact SignsSeen
614-543-1397
FAX: 614-543-9799
TOLL FREE: 1-866-825-4735

- SCROLL display mode of large continuous messages
- ROTATE display mode for rotating of a continuous message
- 8 message moving speeds
- 8 pause periods from 0 to 60 seconds
- 3 kinds of audible beeps during text display
- 61 special international characters
- 4 time and 5 date formats
- Maximum 250 text files and maximum 250 graphic files
- Text memory: 16k Bytes
- 30 schedule tasks - enable by week, month and year
- User friendly interface and programming via IR remote
- RS232 serial interface. Baud rates: 1200/2400/4800/9600/19200/28800
- Password security

Windows-Based Software Included. Download now from our software page.

Support Devices

- Standard Communication: IR Remote / RS232 Serial Input
- Optional: Ethernet Communication
- Optional: Modem

Electrical Specification

Power Source:	120 Volts AC / 60 Hz. or 220VAC
Power Consumption:	Max. 250 Watts (Sign Fully Lit)
Current Draw:	Typ. 1.2 Amps (Fully Lit)
Power Cord Length:	12 Ft. Plug

Physical Specifications

Indoor / Outdoor:	Designed to be Installed and Viewed Indoor
Operating Environment:	32° - 120° F (0° - 49°C) / 0 - 95% Humidity
Dimensions:	39.3" L x 6" H x 3.25" D
Weight:	14 Lbs.

Number of Digits Viewable*:	32 - 1.4" high
*Font and Character Dependant	24 - 2" high
	12 - 4.75" high characters
Character Height:	1.4" / 2" / 4.75" High
Viewing Distance:	1.4" = 60 ft. / 2" = 100 ft. / 4.75" = 200 ft.
LED / Acrylic Face Color:	Red/Green/Amber (Multi-Color)



Contact SignsSeen
614-543-1397
FAX: 614-543-9799
TOLL FREE: 1-866-825-4735

LED Intensity:	10 MCD High-Intensity Digits
LED Life:	Typical 100,000 Hours (10 Years)
UL Listed Power Supply:	Yes
Enclosure Material:	Rugged Aluminum Enclosure
Enclosure Color:	Black Powder-Coat Finish (Scratch Resistant)
Enclosure Rating:	NEMA1 (Standard - Indoor) NEMA12 - Optional - Call for Pricing
Mounting Method:	Brackets Provided for Ceiling/Wall Mount
Limited Warranty:	Factory Service One-Year Parts & Labor - Extended Warranty Available

Applications

Safety Messages	Display Point of Sale Messages
Fault Messages	Display Hours of Operation
Employee Messages	Display Daily Specials
Store Front Messages	Display Holiday Messages
Maintenance Alerts	
Production Alerts	